



<b>LC7131</b>	c-mos LSI	CIRCUIT DRAWING No.4049
PLL FREQUENCY SYNTHESIZER LSI FOR 27MHz CB TRANSCEIVERS		 3008A

**Use**

- PLL frequency synthesizer LSI for 27MHz CB transceiver (U.S. standard, 40ch)

**Functions and Features**

- Built-in high speed programmable divider for direct PLL system.
- PLL out-of-lock output available to inhibit transmission.
- Instantaneous call capability of channel 9, 19
- Built-in detecting circuit of mis-program.
- Built-in amplifier for crystal oscillator.
- Built-in amplifier for active low-pass filter.
- BCD code channel selection. (Pull-down resistors included)


<b>LC7132</b>	c-mos LSI	CIRCUIT DRAWING No.4050
PLL FREQUENCY SYNTHESIZER LSI FOR 27MHz CB TRANSCEIVERS		 3021B

**Use**

PLL frequency synthesizer LSI for 27MHz CB transceivers (U.S. standard).

**Functions and Features**

- Built-in high speed programmable divider for direct PLL system.
- Doubled-frequency of VCO applicable as transmitting frequency carrier.
- PLL out-of-lock output available to inhibit transmission.
- Instantaneous call capability of channel 9.
- Built-in detecting circuit of mis-program.
- Built-in amplifier for crystal oscillator.
- Built-in amplifier for active low-pass filter.
- 7-segment code channel selection. (allowable voltage 15V)

<b>LC7150</b>	c-mos silicon gate LSI	CIRCUIT DRAWING No.4051
PLL FOR CORDLESS TELEPHONE		 3007A

**Functions**

- On-chip PLL for transmission/reception
- On-chip digital unlock detector (only PLL for transmission)
- 5.0kHz/4.4kHz output pins for guard tone
- Standby function

<b>LC7181, 7191</b>	c-mos LSI	CIRCUIT DRAWING No.4052
CB TRANSCEIVER CHANNEL SELECTOR SYSTEM		 3008A

LC7181, 7191 construct 40 channel CB transceiver channel scanning system. The former has an up/down counter for channel memorizing and ROM

for channel output, and the latter has a decoder of channel indication and LED driver.

**Features**

- 40 channel transceiver channel selecting is available by the next means:
  - a. manual scanning
  - b. auto-scanning
  - c. auto-searching
- In the case of the scanning which has indicator on the microphone, connection between a main body and a microphone is realized by means of more added five lines.
- Few noise occurrence because of static driving of LED.
- Capable of instant calling of channel 9 (emergency)
- Stops the channel scanning operation at transmitting.
- 'PA' indication available in the use as a loud speaker.
- Contains LED driver capable of static-driving LED.